



Specifications Philips LED Panel FlexBlend  
SP340P White 27W 3600lm - 940 Cool White |  
120x20cm - UGR <19 - Best Colour Rendering

[View Product](#)

## General Information

|                      |                                       |
|----------------------|---------------------------------------|
| SKU                  | 243297                                |
| EAN                  | 8719514708204                         |
| Manufacturer Code    | 70820400                              |
| Brand                | Philips                               |
| Manufacturer Name    | SP340P 36S/940 SRD PCS U4 SMT L120 WH |
| Budgetlight warranty | 5 Years                               |
| Average Lifetime (h) | 50000                                 |
| Product Serie        | SP340P                                |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x36            |
| Wattage                     | 27W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Yes, Dali       |
| Colour Code                 | 940 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 90-99           |
| Colour of Light             | White           |
| Light Colour Options        | Single Color    |
| Luminous Flux (Lumen)       | 3600lm          |

|                        |                   |
|------------------------|-------------------|
| Lumen per watt         | 133               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Terminal, 5-pole  |
| Powerfactor            | >0.90             |
| Type product           | LED Panel         |

## Fixture Information

|                       |                    |
|-----------------------|--------------------|
| EOC8                  | 70820400           |
| Mounting Method       | Suspendu           |
| Unified Glare Rating  | < 19 - For offices |
| Optische Afdekking    | PC (Polycarbonate) |
| Bedrijfstemperatuur   | -10 to +25         |
| Emergency Lighting    | No                 |
| Colour of the Fixture | White              |
| Housing               | Steel              |
| Colour of material    | White              |

## Dimensions

|                       |          |
|-----------------------|----------|
| Afmetingen LED Paneel | 120x20cm |
| Length (mm)           | 1200     |
| Width (mm)            | 200      |
| Height (mm)           | 73       |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**